

NON-INSULATED RING TERMINALS



ITEM NO	DIMENSIONS inch(mm)					STUD SIZE	WIRE RANGE A.W.G. mm ²
	BRAZED SEAM	d1	d2	B	L		
ITFT-R1.25-3B	0.074(1.9)	0.126(3.2)	0.217(5.5)	0.453(11.5)	0.030(0.75)	#4	22-16 A.W.G. 0.5-1.5 mm ²
ITFT-R1.25-3.5B		0.146(3.7)	0.217(5.5)	0.453(11.5)		#6	
ITFT-R1.25-4B		0.169(4.3)	0.315(8.0)	0.622(15.8)		#8	
ITFT-R1.25-4MB		0.169(4.3)	0.260(6.6)	0.567(14.4)		#8	
ITFT-R1.25-5B		0.209(5.3)	0.315(8.0)	0.622(15.8)		#10	
ITFT-R1.25-6B		0.252(6.4)	0.457(11.6)	0.846(21.5)		1/4	
ITFT-R1.25-8B		0.331(8.4)	0.457(11.6)	0.846(21.5)		5/16	
ITFT-R1.25-10B		0.413(10.5)	0.539(13.7)	1.004(25.5)		3/8	
ITFT-R1.25-12B		0.512(13.0)	0.748(19.0)	1.130(28.7)		1/2	
ITFT-R2-3B	0.098(2.5)	0.126(3.2)	0.335(8.5)	0.661(16.8)	0.031(0.80)	#4	16-14 A.W.G. 1.5-2.5 mm ²
ITFT-R2-3.5B		0.146(3.7)	0.26(6.6)	0.567(14.4)		#6	
ITFT-R2-4B		0.169(4.3)	0.335(8.5)	0.661(16.8)		#8	
ITFT-R2-4MB		0.169(4.3)	0.260(6.6)	0.567(14.4)		#8	
ITFT-R2-5B		0.209(5.3)	0.374(9.5)	0.657(16.7)		#10	
ITFT-R2-5MB		0.209(5.3)	0.335(8.5)	0.661(16.8)		#10	
ITFT-R2-6B		0.252(6.4)	0.472(12.0)	0.835(21.2)		1/4	
ITFT-R2-8B		0.331(8.4)	0.472(12.0)	0.835(21.2)		5/16	
ITFT-R2-10B		0.413(10.5)	0.539(13.7)	1.004(25.5)		3/8	
ITFT-R2-12B	0.512(13.0)	0.748(19.0)	1.130(28.7)	1/2			
ITFT-R5.5-3.5B	0.141(3.6)	0.146(3.7)	0.374(9.5)	0.756(19.2)	0.039(1.0)	#6	12-10 A.W.G. 4-6 mm ²
ITFT-R5.5-4B		0.169(4.3)	0.374(9.5)	0.756(19.2)		#8	
ITFT-R5.5-4SB		0.169(4.3)	0.291(7.4)	0.728(18.5)		#8	
ITFT-R5.5-5B		0.209(5.3)	0.374(9.5)	0.756(19.2)		#10	
ITFT-R5.5-6B		0.252(6.4)	0.472(12.0)	1.004(25.5)		1/4	
ITFT-R5.5-8B		0.331(8.4)	0.591(15.0)	1.091(27.7)		5/16	
ITFT-R5.5-10B		0.413(10.5)	0.591(15.0)	1.091(27.7)		3/8	

Packaging: 100 pcs per packet

Pages.1/2

NON-INSULATED RING TERMINALS



ITEM NO	DIMENSIONS inch(mm)					STUD SIZE	WIRE RANGE A.W.G. mm ²
	BRAZED SEAM	d1	d2	B	L		
ITFT-R8-5B		0.193(4.9)	0.205(5.2)	0.437(11.1)	0.886(22.5)	0.039(1.00)	8 A.W.G.
ITFT-R8-8B		0.189(4.8)	0.339(8.6)	0.551(14.0)	1.063(27.0)		5/16

Features

1. Terminal material is Copper (instead of Brass).
2. Quality "brazed seam" does not separate during crimping.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.