

PVC-INSULATED RING TERMINALS (EASY ENTRY)



ITEM NO	DIMENSIONS inch(mm)				STUD SIZE	WIRE RANGE A.W.G. mm ²		
	BUTTED SEAM	B	d2	L			t	
ITFT-VER1.25-3.5		0.217(5.50)	0.146(3.70)	0.728(18.50)	0.030 (0.75)	22-16 A.W.G. 0.5-1.5 mm ²		
ITFT-VER1.25-4		0.315(8.00)	0.169(4.30)	0.894(22.70)				
ITFT-VER1.25-4M		0.260(6.60)	0.169(4.30)	0.843(21.40)				
ITFT-VER1.25-5		0.315(8.00)	0.209(5.30)	0.894(22.70)				
ITFT-VER1.25-6		0.457(11.60)	0.252(6.40)	1.126(28.60)				
ITFT-VER1.25-8		0.457(11.60)	0.331(8.40)					
ITFT-VER1.25-10		0.539(13.70)	0.413(10.50)	1.280(32.50)			0.031 (0.80)	16-14 A.W.G. 1.5-2.5 mm ²
ITFT-VER2-3.5		0.260(6.60)	0.146(3.70)	0.846(21.50)				
ITFT-VER2-4		0.335(8.50)	0.169(4.30)	0.925(23.50)				
ITFT-VER2-4M		0.260(6.60)	0.169(4.30)	0.839(21.30)				
ITFT-VER2-5		0.374(9.50)	0.209(5.30)	0.925(23.50)				
ITFT-VER2-5M		0.335(8.50)	0.209(5.30)					
ITFT-VER2-6		0.472(12.00)	0.252(6.40)	1.126(28.60)				
ITFT-VER2-8		0.472(12.00)	0.331(8.40)					
ITFT-VER2-10		0.539(13.70)	0.413(10.50)	1.276(32.40)				
ITFT-VER2-12		0.748(19.00)	0.512(13.00)	1.421(36.10)				
ITFT-VER5.5-3.5		0.374(9.50)	0.146(3.70)	1.102(28.00)	0.039 (1.00)	12-10 A.W.G. 4-6 mm ²		
ITFT-VER5.5-4		0.374(9.50)	0.169(4.30)	1.102(28.00)				
ITFT-VER5.5-4S		0.291(7.40)	0.169(4.30)	1.075(27.30)				
ITFT-VER5.5-5		0.374(9.50)	0.209(5.30)	1.102(28.00)				
ITFT-VER5.5-6		0.472(12.00)	0.252(6.40)	1.339(34.00)				
ITFT-VER5.5-8		0.591(15.00)	0.331(8.40)	1.437(36.50)				
ITFT-VER5.5-10		0.591(15.00)	0.413(10.50)					
ITFT-VER5.5-12		0.756(19.20)	0.512(13.00)	1.634(41.50)				

Packaging: 100 pcs per packet

Features

1. Terminal material is Copper (instead of Brass).
2. Easy-entry/Funnel-entry advantage.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.