

PVC-INSULATED SPADE TERMINALS (EASY ENTRY)



ITEM NO	DIMENSIONS inch (mm)				STUD SIZE	WIRE RANGE A.W.G. mm ²
	BUTTED SEAM	B	d2	L		
ITFT-VES1.25-3.5S	0.224(5.70)	0.146(3.70)	0.906(23.00)	0.030 (0.75)	#6	22-16 A.W.G. 0.5-1.5 mm ²
ITFT-VES1.25-4	0.283(7.20)	0.169(4.30)				
ITFT-VES1.25-4S	0.252(6.40)	0.169(4.30)				
ITFT-VES1.25-5	0.315(8.00)	0.209(5.30)				
ITFT-VES1.25-6	0.421(10.70)	0.252(6.40)	0.945(24.00)	1/4		
ITFT-VES1.25-6S	0.366(9.30)	0.252(6.40)		1/4		
ITFT-VES2-3	0.224(5.70)	0.126(3.20)	0.906(23.00)	0.031 (0.80)	#4	16-14 A.W.G. 1.5-2.5 mm ²
ITFT-VES2-3.5S	0.224(5.70)	0.126(3.20)				
ITFT-VES2-4S	0.252(6.40)	0.169(4.30)				
ITFT-VES2-5	0.315(8.00)	0.209(5.30)				
ITFT-VES2-6	0.421(10.70)	0.252(6.40)	0.945(24.00)	1/4		
ITFT-VES2-6S	0.366(9.30)	0.252(6.40)		1/4		
ITFT-VES5.5-3	0.287(7.30)	0.126(3.20)	1.091(27.70)	0.039 (1.00)	#4	12-10 A.W.G. 4-6 mm ²
ITFT-VES5.5-3.5S	0.248(6.30)	0.146(3.70)				
ITFT-VES5.5-4	0.323(8.20)	0.169(4.30)				
ITFT-VES5.5-5	0.354(9.00)	0.209(5.30)				
ITFT-VES5.5-6	0.472(12.00)	0.252(6.40)	1.248(31.70)	1/4		
ITFT-VES5.5-6S	0.354(9.00)	0.252(6.40)		1/4		

Packaging: 100 pcs per packet

Features

1. Terminal material is Copper (instead of Brass).
2. Easy-entry/Funnel-entry advantage.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.