

OPT HAND CRIMPING TOOLS

For Insulated Terminal & Connector

Ratchet type.

| Model | Crimping Range (mm ²) | Weight (kg) | Length (mm) |
|-------------|-----------------------------------|-------------|-------------|
| TOPT-LY-03C | 0.5 - 6 | 0.6 | 230 |
| TOPT-AN-03C | 0.5 - 6 | 0.6 | 230 |
| TOPT-FN-03C | 0.5 - 6 | 0.6 | 230 |
| TOPT-SN-02C | 0.25 – 2.5 | 0.35 | 190 |



TOPT-LY-03C

- R: 0.5-1.5mm² AWG20-16
- B: 2.5mm² AWG14
- Y: 4-6mm² AWG12-10



TOPT-AN-03C



TOPT-FN-03C

- G: 0.25-0.5mm² AWG24-20
- R: 0.75-1.5mm² AWG18-16
- B: 2.0-2.5mm² AWG14



TOPT-SN-02C

For Multipurpose Application

Tool Set of TOPT-LY-03C plus 4 additional dies.

| Model | Crimping Dies Model | Crimping Range (mm ²) |
|----------------|---|-----------------------------------|
| TOPT-LY-03C-5D | Dies (TOPT-LY-03C) For Insulated Terminal & Connector | 0.5 – 6 |
| | Dies (TOPT-LY-03B) For Non-insulated Receptacle & Tab Terminal | 0.5 – 6 |
| | Dies (TOPT-LY-04WF) Dies (TOPT-LY-16WF) For Wire Ferrules & End Sleeves | 0.5 – 4 6 – 16 |
| | Dies (TOPT-LY-10) For Non-insulated Terminal | 1.5 - 10 |



TOPT-LY-03C-5D

For Non-Insulated Receptable & Tab Terminal

Ratchet type.

Tab Width = 6.3mm

| Model | Crimping Range (mm ²) | Weight (kg) | Length (mm) |
|-------------|-----------------------------------|-------------|-------------|
| TOPT-LY-03B | 0.5 - 6 | 0.6 | 230 |



TOPT-LY-03B