

PVC-INSULATED RING TERMINALS (EASY ENTRY)



ITEM NO	DIMENSIONS inch(mm)				STUD SIZE	WIRE RANGE A.W.G. mm ²	
	BUTTED SEAM	B	d2	L			t
ITFT-VER1.25-3		0.217(5.50)	0.126(3.20)	0.728(18.50)	#4	22-16 A.W.G. 0.5-1.5 mm ²	
ITFT-VER1.25-3.5		0.217(5.50)	0.146(3.70)		#6		
ITFT-VER1.25-4		0.315(8.00)	0.169(4.30)	0.894(22.70)	#8		
ITFT-VER1.25-4M		0.260(6.60)	0.169(4.30)	0.843(21.40)	#8		
ITFT-VER1.25-5		0.315(8.00)	0.209(5.30)	0.894(22.70)	#10		
ITFT-VER1.25-6		0.457(11.60)	0.252(6.40)	1.126(28.60)	1/4		
ITFT-VER1.25-8		0.457(11.60)	0.331(8.40)		5/16		
ITFT-VER1.25-10		0.539(13.70)	0.413(10.50)	1.280(32.50)	3/8		
ITFT-VER2-3		0.335(8.50)	0.126(3.20)	0.846(21.50)	#4		16-14 A.W.G. 1.5-2.5 mm ²
ITFT-VER2-3.5		0.260(6.60)	0.146(3.70)	0.846(21.50)	#6		
ITFT-VER2-4		0.335(8.50)	0.169(4.30)	0.925(23.50)	#8		
ITFT-VER2-4M		0.260(6.60)	0.169(4.30)	0.839(21.30)	#8		
ITFT-VER2-5		0.374(9.50)	0.209(5.30)	0.925(23.50)	#10		
ITFT-VER2-5M		0.335(8.50)	0.209(5.30)		#10		
ITFT-VER2-6		0.472(12.00)	0.252(6.40)	1.126(28.60)	1/4		
ITFT-VER2-8		0.472(12.00)	0.331(8.40)		5/16		
ITFT-VER2-10		0.539(13.70)	0.413(10.50)	1.276(32.40)	3/8		
ITFT-VER2-12		0.748(19.00)	0.512(13.00)	1.421(36.10)	1/2		

PVC-INSULATED RING TERMINALS (EASY ENTRY)



ITEM NO	DIMENSIONS inch(mm)				STUD SIZE	WIRE RANGE A.W.G. mm ²
	BUTTED SEAM	B	d2	L		
ITFT-VER5.5-3.5		0.374(9.50)	0.146(3.70)	1.102(28.00)	0.039 (1.00)	12-10 A.W.G. 4-6 mm ²
ITFT-VER5.5-4		0.374(9.50)	0.169(4.30)	1.102(28.00)		
ITFT-VER5.5-4S		0.291(7.40)	0.169(4.30)	1.075(27.30)		
ITFT-VER5.5-5		0.374(9.50)	0.209(5.30)	1.102(28.00)		
ITFT-VER5.5-6		0.472(12.00)	0.252(6.40)	1.339(34.00)		
ITFT-VER5.5-8		0.591(15.00)	0.331(8.40)	1.437(36.50)		
ITFT-VER5.5-10		0.591(15.00)	0.413(10.50)			
ITFT-VER5.5-12		0.756(19.20)	0.512(13.00)			

Packaging: 100pcs per packet.

Features:

1. Terminal material is Copper (instead of Brass).
2. Easy-entry/Funnel-entry advantage.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.