

OPT HAND CUTTER

Model	Application	Range	Weight (kg)	Length (mm)
TOPT-AC-210	Spring Wire	4.5mm Ø	2.1	600
	Cable	150mm ²		
	Steel Bar	9mm Ø		
	ACSR	15mm Ø		

AC-210 ACSR & Rod & Wire



Model	Application	Range	Weight (kg)	Length (mm)
TOPT-MK-250	Copper Cable	250mm ²	1.6	600
	Aluminium Cable			

TOPT-MK-250



OPT CABLE KNIFE

Model	Features	Length (mm)
TOPT-KN-20B	SK5 Blade	180
TOPT-KN-070103	1000V Insulated	200
TOPT-KN-070104	1000V Insulated	430



KN-070103



TOPT-KN-070104

OPT CABLE TIE GUN

Model	Width of Cable Tie (mm)	Length (mm)
TOPT-LY-600N	Max 7.9 Thickness 0.3mm	180
TOPT-LY-600F	4.5 – 12	200



With TPR Trigger Handle

Tension Indicator

TPR Tension Dial

TOPT-LY-600N

Adjustable tension dial for 4 levels building pressure. Automatic cut-off once required tension is achieved. Made of Metal / Aluminium frame construction.

TOPT-LY-600F

For BCT Type Stainless Steel Cable Tie

