

OPT HYDRAULIC CABLE CUTTER

TOPT-CPC-85A Hydraulic Cable Cutter

- Applications : Cutting of Copper & Aluminium PVC Cable
- Output Force : 5 Tons
- Cutting Range : Bare Copper Wire Strand Max. O.D. 28 mm
 Bare Aluminium Wire Strand Max. O.D. 38 mm
 CCP Cable Max. O.D. 85 mm
 Underground Cable Max O.D. 50 mm
- Total Length : 695mm
- Weight : 7kgs
- Remark : Free Pin Design
- Note** : **DO NOT use it to cut any rebar, steel wire or armoured cables.**



TOPT-HT-85 Hydraulic Cable Cutter Head

- Applications : Cutting of Copper & Aluminium PVC Cable
- Input Pressure : Max. 700bar or 10,000psi
- Opening Jaw : 85mm
- Cutting Range : Up to 85mm OD (for Telephone Cu/Al Cable)
 Up to 50mm OD (for Underground Cable)
- Length : 456mm
- Weight : 6kgs
- Note** : **DO NOT use it to cut any rebar, steel wire or armoured cables.**



TOPT-S-100H Hydraulic Cable Cutter Head

- Applications : Cutting of Copper & Aluminium Cable including Armoured Cable
- Input Pressure : Max. 700bar or 10,000psi
- Opening Jaw : 100mm
- Cutting Range : Up to 100mm OD
- Total Length : 570mm
- Weight : 14kgs



Notes:

- S-100H & HT-85 cutters can be paired with CONWAY range of Electric and Hydraulic pumps:
 - TCPM-1000
 - TCCP-630HP
 - TCCP-630FP
 - TOPT-F-B



After sales service support and spare parts are available.