

PVC-INSULATED FEMALE DISCONNECTS



ITEM NO	DIMENSIONS inch(mm)					WIRE RANGE A.W.G. mm ²
	TAB SIZE	D	B	L	t	
ITFT-VF1.25-110(5)	0.110*0.020 2.8*0.5	0.142(3.60)	0.126(3.20)	0.728(18.50)	0.010(0.25)	22-16 A.W.G. 0.5-1.5 mm ²
ITFT-VF1.25-187(5)	0.187*0.020 4.8*0.5		0.197(5.00)	0.728(18.50)	0.016(0.40)	
ITFT-VF1.25-250	0.250*0.032 6.4*0.8		0.264(6.70)	0.807(20.50)		
ITFT-VF2-110(5)	0.110*0.020 2.8*0.5	0.173(4.40)	0.126(3.20)	0.728(18.50)	0.010(0.25)	16-14 A.W.G. 1.5-2.5 mm ²
ITFT-VF2-187(5)	0.187*0.020 4.8*0.5		0.197(5.00)	0.728(18.50)	0.016(0.40)	
ITFT-VF2-250	0.250*0.032 6.4*0.8		0.264(6.70)	0.807(20.50)		
ITFT-VF5.5-250	0.250*0.032 6.4*0.8	0.213(5.40)	0.264(6.70)	0.925(23.50)		12-10 A.W.G. 4-6 mm ²

Packaging: 100 pcs per packet.

Features :

1. Terminal material is Copper (instead of Brass).
2. Easy-entry/Funnel-entry advantage.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.