

NYLON-INSULATED TWIN CORD END TERMINALS



ITEM NO	DIMENSIONS inch(mm)				COLOUR	WIRE RANGE A.W.G. mm ²
	W	D1	L	t		
ITFT-CT205008	0.185(4.70)	0.059(1.5)	0.591(15.00)	0.006 (0.15)	ORANGE	2*22 A.W.G 2*0.5mm ²
ITFT-CT207508	0.197(5.00)	0.071(1.80)	0.591(15.00)		WHITE	2*22 A.W.G 2*0.75mm ²
ITFT-CT210008	0.213(5.40)	0.081(2.05)	0.591(15.00)		YELLOW	2*18 A.W.G 2*1.0mm ²
ITFT-CT215008	0.260(6.60)	0.087(2.20)	0.630(16.00)		RED	2*16 A.W.G 2*1.5mm ²
ITFT-CT225010	0.307(7.80)	0.110(2.8)	0.728(18.50)	0.008 (0.20)	BLUE	2*14 A.W.G 2*2.5mm ²
ITFT-CT240012	0.346(8.80)	0.146(3.70)	0.906(23.00)		GREY	2*12 A.W.G 2*4.0mm ²
ITFT-CT260014	0.394(10.00)	0.189(4.80)	1.024(26.00)		BLACK	2*10 A.W.G 2*6.0mm ²
ITFT-CT210014	0.512(13.00)	0.252(6.40)	1.024(26.00)		IVORY	2*8 A.W.G 2*10mm ²
ITFT-CT216014	0.724(18.40)	0.327(8.30)	1.181(30.00)	0.012 (0.30)	GREEN	2*6 A.W.G 2*16mm ²

Packaging: 100 pcs per packet

Features

1. Terminal material is Copper (instead of Brass).
2. Easy-entry/Funnel-entry advantage.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.