

PVC-INSULATED PIGGYBACK DISCONNECTS



| ITEM NO | DIMENSIONS inch(mm) | | | | | | WIRE RANGE A.W.G. mm ² |
|------------------|---------------------|-------------|-----------------|--------------|-----------------|-----------------|---|
| | TAB SIZE | D | B | L | b | t | |
| ITFT-VPB1.25-250 | 0.250*0.032 | 0.142(3.60) | 0.264 (6.70) | 0.886(22.50) | 0.244 (6.20) | 0.016 (0.40) | 22-16 A.W.G. 0.5-1.5 mm ² |
| | 6.4*0.8 | | | | | | |
| ITFT-VPB2-250 | 0.250*0.032 | 0.173(4.40) | 0.264 (6.70) | 0.965(24.50) | 0.244 (6.20) | 0.016 (0.40) | 16-14 A.W.G. 1.5-2.5 mm ² |
| | 6.4*0.8 | | | | | | |
| ITFT-VPB5.5-250 | 0.250*0.032 | 0.213(5.40) | 0.264 (6.70) | 0.965(24.50) | 0.244 (6.20) | 0.016 (0.40) | 12-10 A.W.G. 4-6 mm ² |
| | 6.4*0.8 | | | | | | |

Packaging: 100 pcs per packet

Features

1. Terminal material is Copper (instead of Brass).
2. Easy-entry/Funnel-entry advantage.
3. UL Listed (E163810 & E318463).
4. RoHS Compliant.
5. REACH Compliant.