

# **CAST RESIN STRAIGHT JOINT**

## For 4-core unarmoured cables with PVC and XLPE Insulation up to 1kV

MELEC Cast Resin Straight Joint (splicing kits) are suitable for indoor, outdoor (weather exposed) and underground or submersed application. The resin formulation is electrical grade and offers good adhesion to plastic, PVC, XLPE and metals. The cured resin is durable and protects the joint against moisture, oil and other type of chemicals.

#### Main features:

- Compact dimensions
- High quality transparent shell
- Corrosion resistance
- UV and weathering resistance
- Good electrical and mechanical properties
- Ease of installation
- Safe and non-toxic components
- Wide range of cable sizes coverage

#### Package List:

- 1. Transparent plastic shell
- 2. Cast resin two components
- 3. Sand-cloth paper
- 4. PVC tape
- 5. Installation instructions




Also suitable for armoured cables (Grounding insulated power cables and constant force springs to be purchased separately.)

### **Sizing Range**

Item Code	Description	Conductor Size Range (mm²)
KLLV-CRSJ-M11	MELEC LV Cast Resin Straight Joint 4C 4-10mm <sup>2</sup>	4 - 10
KLLV-CRSJ-M12	MELEC LV Cast Resin Straight Joint 4C 10-25mm²	10 - 25
KLLV-CRSJ-M13	MELEC LV Cast Resin Straight Joint 4C 25-50mm²	25 - 50
KLLV-CRSJ-M14	MELEC LV Cast Resin Straight Joint 4C 50-95mm²	50 - 95
KLLV-CRSJ-M15	MELEC LV Cast Resin Straight Joint 4C 95-150mm²	95 - 150
KLLV-CRSJ-M16	MELEC LV Cast Resin Straight Joint 4C 150-240mm <sup>2</sup>	150 - 240

Note: Shelf life of the cast resin is 36 months at ambient temperature between 15°C to 35°C.









Tel H/P

: +6 03 5569 0600 : +6 012 506 1068 Email : ask@conway.com.my

Web: www.conway.com.my