

MV HEAT SHRINK TERMINATION KITS INDOOR

Medium Voltage Heat Shrink Termination Kits are designed for indoor application on single and three-core non armoured cables (XLPE, PVC and PE) for 11kV.

Main features :

- Reliable stress control
- Large cross-section range
- Excellent corrosion resistance
- UV resistance and weathering resistance
- Anti-tracking
- Superior electrical and mechanical properties
- Easy installation



1C Indoor



3C Indoor

11kV 1C Indoor

Item Code	Description	Conductor Size Range (mm ²)
KMME-MZDN-1X3-11-50-95	MV HS Termination Indoor 11kV 1C 50-95mm ²	50 - 95
KMME-MZDN-1X3-11-95-240	MV HS Termination Indoor 11kV 1C 95-240mm ²	95 - 240
KMME-MZDN-1X3-11-300-500	MV HS Termination Indoor 11kV1C 300-500mm ²	300 - 500
KMME-MZDN-1X3-11-630-1000	MV HS Termination Indoor 11kV 1C 630-1000mm ²	630 - 1000

11kV 3C Indoor

Item Code	Description	Conductor Size Range (mm ²)
KMME-MZDN-3-11-50-95	MV HS Termination Indoor 11kV 3C 50-95mm ²	50 - 95
KMME-MZDN-3-11-95-240	MV HS Termination Indoor 11kV 3C 95-240mm ²	95 - 240
KMME-MZDN-3-11-150-300	MV HS Termination Indoor 11kV 3C 150-300mm ²	150 - 300

Notes:

Mechanical Lugs are applicable for below cross-sections. Lugs are not included in the kits. Refer to Mechanical Lugs product brochure for more information.