

MV HEAT SHRINK TERMINATION KITS OUTDOOR

Medium Voltage Heat Shrink Termination Kits are designed for outdoor application on single and three-core non armoured cables (XLPE, PVC and PE) for 11kV.

Main features:

- Reliable stress control
- Large cross-section range
- Excellent corrosion resistance
- UV resistance and weathering resistance
- Anti-tracking
- Superior electrical and mechanical properties
- Easy installation


1C Outdoor

3C Outdoor
11kV 1C Outdoor

Item Code	Description	Conductor Size Range (mm ²)
KMME-MZDW-1X3-11-50-95	MV HS Termination Outdoor 11kV 1C 50-95mm ²	50 - 95
KMME-MZDW-1X3-11-95-240	MV HS Termination Outdoor 11kV 1C 95-240mm ²	95 - 240
KMME-MZDW-1X3-11-300-500	MV HS Termination Outdoor 11kV1C 300-500mm ²	300 - 500
KMME-MZDW-1X3-11-630-1000	MV HS Termination Outdoor 11kV 1C 630-1000mm ²	630 - 1000

11kV 3C Outdoor

Item Code	Description	Conductor Size Range (mm ²)
KMME-MZDW-3-11-16-35	MV HS Termination Outdoor 11kV 3C 16-35mm ²	16 - 35
KMME-MZDW-3-11-50-95	MV HS Termination Outdoor 11kV 3C 50-95mm ²	50 - 95

Notes:

Mechanical Lugs are applicable for below cross-sections. Lugs are not included in the kits. Refer to Mechanical Lugs product brochure for more information.