

OPT HAND CRIMPING TOOLS

For Insulated Terminal & Connector

Ratchet type.

Model	Crimping Range (mm ²)	Weight (kg)	Length (mm)
TOPT-LY-03C	0.5 - 6	0.6	230
TOPT-ANB-03C	0.5 - 6	0.6	230
TOPT-FN-03C	0.5 - 6	0.6	230



TOPT-LY-03C

- R: 0.5-1.5mm² AWG20-16
- B: 2.5mm² AWG14
- Y: 4-6mm² AWG12-10



TOPT-ANB-03C



TOPT-FN-03C

For Multipurpose Application (Pre-order)

Tool Set of TOPT-LY-03C plus 4 additional dies.

Model	Crimping Dies Model	Crimping Range (mm ²)
TOPT-LY-03C-5D	Dies (TOPT-LY-03C) For Insulated Terminal & Connector	0.5 - 6
	Dies (TOPT-LY-03B) For Non-insulated Receptacle & Tab Terminal	0.5 - 6
	Dies (TOPT-LY-04WF) Dies (TOPT-LY-16WF) For Wire Ferrules & End Sleeves	0.5 - 4 6 - 16
	Dies (TOPT-LY-10) For Non-insulated Terminal	1.5 - 10



TOPT-LY-03C-5D

For Non-Insulated Receptable & Tab Terminal

Ratchet type.

Tab Width = 6.3mm

Model	Crimping Range (mm ²)	Weight (kg)	Length (mm)
TOPT-LY-03B	0.5 - 6	0.6	230



TOPT-LY-03B