

# OPT HAND CRIMPING TOOLS

## For Open Barrel Terminal & Non-insulated Receptable Tab Terminal

Model	Tab Width (mm)	Crimping Range (mm <sup>2</sup> )	Weight (kg)	Length (mm)
TOPT-SN-28B	2.8	0.25 - 1	0.35	190



TOPT-SN-28B

## For Cable Lug / Non-insulated Terminal

Ratchet type. PVC handle. Smart open-knob.

Model	Crimping Range (mm <sup>2</sup> )	Weight (kg)	Length (mm)
TOPT-KH-6	0.75 - 6	0.23	195
TOPT-KH-8	1.5 - 10	0.6	250
TOPT-KH-16	1.5 - 16	0.6	280
TOPT-KH-22	6 - 25	0.92	365
TOPT-KH-38	6 - 35	0.92	365



TOPT-KH-6



TOPT-KH-16



TOPT-KH-8



TOPT-KH-22 & TOPT-KH-38

## For Copper Cable Lug and Link

With Non-ratchet Adjusting Screw.  
Indent Crimping.

Model	Crimping Range (mm <sup>2</sup> )	Weight (kg)	Length (mm)
TOPT-KH-120	10 - 95	2.8	558
TOPT-KH-150	10 - 120	3.5	595



TOPT-KH-120



TOPT-KH-150