

# HEAT SHRINK TERMINATION KITS (INDOOR)

Medium Voltage Heat Shrink Termination kits are designed for reliable indoor termination of 11kV single and three-core non-armoured cables (XLPE, PVC and PE)

## Main features:

- Reliable stress control
- Wide cross-section range
- Excellent corrosion resistance
- UV and weather resistance
- Anti-tracking performance
- Superior electrical and mechanical properties
- Easy installation



1C Indoor

3C Indoor

## 11kV 1C Indoor

| Item Code                 | Description                                                     | Size Range (mm <sup>2</sup> ) |
|---------------------------|-----------------------------------------------------------------|-------------------------------|
| KMME-MZDN-1X3-11-50-95    | CONWAY 11kV 1C 50-95mm <sup>2</sup> MV HS Termination Indoor    | 50 - 95                       |
| KMME-MZDN-1X3-11-95-240   | CONWAY 11kV 1C 95-240mm <sup>2</sup> MV HS Termination Indoor   | 95 - 240                      |
| KMME-MZDN-1X3-11-300-500  | CONWAY 11kV 1C 300-500mm <sup>2</sup> MV HS Termination Indoor  | 300 - 500                     |
| KMME-MZDN-1X3-11-630-1000 | CONWAY 11kV 1C 630-1000mm <sup>2</sup> MV HS Termination Indoor | 630 - 1000                    |

## 11kV 3C Indoor

| Item Code              | Description                                                    | Size Range (mm <sup>2</sup> ) |
|------------------------|----------------------------------------------------------------|-------------------------------|
| KMME-MZDN-3-11-50-95   | CONWAY 11kV 3C 50-95mm <sup>2</sup> MV HS Termination Indoor   | 50 - 95                       |
| KMME-MZDN-3-11-95-240  | CONWAY 11kV 3C 95-240mm <sup>2</sup> MV HS Termination Indoor  | 95 - 240                      |
| KMME-MZDN-3-11-150-300 | CONWAY 11kV 3C 150-300mm <sup>2</sup> MV HS Termination Indoor | 150 - 300                     |

## Note:

1. Mechanical Lugs are applicable for use with above kits but are not included. Please refer to the Mechanical Lugs brochure for more information.
2. Please contact our sales consultant before placing your order.