

HEAT SHRINK TERMINATION KITS (OUTDOOR)

Medium Voltage Heat Shrink Termination kits are designed for reliable outdoor termination of 11kV single and three-core non-armoured cables (XLPE, PVC and PE)

Main features:

- Reliable stress control
- Wide cross-section range
- Excellent corrosion resistance
- UV and weather resistance
- Anti-tracking performance
- Superior electrical and mechanical properties
- Easy installation



1C Outdoor



3C Outdoor

11kV 1C Outdoor

Item Code	Description	Size Range (mm ²)
KMME-MZDN-1X3-11-50-95	CONWAY 11kV 1C 50-95mm ² MV HS Termination Outdoor	50 - 95
KMME-MZDN-1X3-11-95-240	CONWAY 11kV 1C 95-240mm ² MV HS Termination Outdoor	95 - 240
KMME-MZDN-1X3-11-300-500	CONWAY 11kV 1C 300-500mm ² MV HS Termination Outdoor	300 - 500
KMME-MZDN-1X3-11-630-1000	CONWAY 11kV 1C 630-1000mm ² MV HS Termination Outdoor	630 - 1000

11kV 3C Outdoor

Item Code	Description	Size Range (mm ²)
KMME-MZDN-3-11-16-35	CONWAY 11kV 3C 16-35mm ² MV HS Termination Outdoor	16 - 35
KMME-MZDN-3-11-50-95	CONWAY 11kV 3C 50-95mm ² MV HS Termination Outdoor	50 - 95

Note:

1. Mechanical Lugs are applicable for use with above kits but are not included. Please refer to the Mechanical Lugs brochure for more information.
2. Please contact our sales consultant before placing your order.